

# Prevent Damage to Chrome Clad Wheels

GM Service Bulletin #09-03-10-016 recommends using an adjustable flange plate to safely mount and prevent finish damage to Chrome Clad or ChromeTech® wheels when performing balancing service.

**Order a Hunter Adjustable Flange Plate Today!**

**Hunter's Adjustable Flange Plate & Stud Kit**

**Order 700-20-1839-1**


Single-plate, sliding bolt circle design with interchangeable pins provides quick setup and universal fitment.




## Added Protection of Direct-Fit Collets

Further protect chrome clad wheels and gain improved mounting accuracy with Hunter's Direct-Fit Collets.

Direct-Fit Collets accurately mount the wheel on the hub bore and do not contact the chrome cladding.



Typical high-taper cones protrude through the hub bore, contacting the chrome cladding and preventing proper mounting of the wheel on the hub bore.



**Precision Mounting Kit**

**Order 700-20-2472-1**

Includes Adjustable Flange Plate Kit; 8 double-sided, direct-fit collets; collet selection gauges; spacer ring; and clamping cup.



**Precision Collet Kit**

**Order 700-20-2474-1**

Includes 8 double-sided, direct-fit collets and collet selection gauges.



**Call for Pricing!**



**To order, call 1-800-GM-TOOLS or visit GMDEsolutions.com**

**HUNTER Engineering Company**

Promo #GM10-109.

Products are sold F.O.B. Shipping Point.

**Pricing effective through September 30, 2010.**

Form 6163-T, 03-10