

WiScope™

inspect the inside

- True High Definition Imaging
- Interchangeable Imagers-For Application Flexibility
- Easy to use, easy to connect
- Superior LED light control to reduce glare on shiny objects, i.e. pistons



WiScope™

Specifications



General	Power supply	Li-ion rechargeable battery
	Durability	Cycle tested 75,000 cycles
	Autonomy	
Dimensions and weight	Charge time	5 hours (from empty)
	Length	1.77" - 45 mm
	Width	3.07" - 78 mm
	Height	6" - 152 mm
	Weight	.4 lbs - 170 grams
Imagers	Interchangeable	CFAST connector
	∅ 3.8 mm forward view 1 m	
	∅ 3.8 mm side view 1 m	
	∅ 5.5 mm dual view 1 m	
	∅ 5.5 mm articulating forward view 24 inch	
Connectivity	∅ 8.5 mm dual view UV 1 m	
	Wireless interface	Wifi 802.11N
	Wireless range	100 feet
Video	Resolution	720P
	Stream rate	15-25 frames per second
	Zoom	
Application support	Android	

WiScope™

WiScope Imager Versatility



ø 3.8 mm
Forward View
1 m



ø 8.5 mm
Dual View UV
1 m



ø 8.5 mm
Dual View
1 m
3 m



ø 5.5 mm
Dual View
1 m

Articulating



ø 5.5 mm
Forward View
1 m

WiScope™

applications

The more imagers, the more applications. With interchangeable imagers, the WiScope is the choice for these inspections and more:

- Valve Inspections
- Cylinder Inspections
- Combustion Chamber Inspections
- Water Pump Inspections
- Axle Inspections
- Gasket Integrity Inspections
- Gasket Leak
- Transmission (Automatic/Manual)
- Cam Shaft Inspection
- Electrical and Wiring Inspections
- Injector Inspections
- Belt/Hose/Pulley Inspections

